

ALPHA

High output LED high bay



Features:

High output LED high bay, ideal for production and warehouse areas

Available in 3 sizes and 4 outputs

CRI: Ra>80

Up to 146 lumens per Watt efficacy

50,000 hours lifetime (L70/B50)

Construction:

Die-cast aluminium body

Available in Black (RAL 9005)

Separate stirrup mounting bracket available

Integral driver

Supplied as standard with neutral white (4000K) LED

Options:

No options available

ALPHA

High output LED high bay

Order Codes



All dimensions are in millimetres

Order code	Description	Lumens (lm)	Total power (W)	Efficacy (lm/W)	Weight (kg)
ALP1460WNW	100W - 4000K	14600	100	146	2.64
ALP1900WNW	150W - 4000K	19000	150	127	3.10
ALP2610WNW	200W - 4000K	26100	200	131	4.50
ALP3130WNW	240W - 4000K	31300	240	130	4.54

Dimensions

All dimensions are in millimetres

Order code	C	Diameter
ALP1460WNW	160	270
ALP1900WNW	180	300
ALP2610WNW	180	330
ALP3130WNW	180	330



Installation instructions:

Suspended via hook (supplied) and supplied with 1.5m of 3-core black mains flex

To specify:

LED High bay as per Tamlite ALPHA range

Please Note: Order codes listed are for standard (non-emergency) versions only. For all other gear options, please contact Tamlite Lighting.